



IPSO®

HIGH-EFFICIENT SOFTMOUNT WASHER-EXTRACTORS

IY180 | IY240 | IY280

FEATURES

- Freestanding, high spin
- Fully programmable Aries controller
- Integrated detergent signal board
- Integrated programmable heating elements
- Stainless steel top and front panel, black side panels
- Stainless steel drum and tub
- High capacity water inlets
- Large gravity drain (Ø 76 mm)
- Large door opening for easy loading & unloading



visit laundrysolutions.com.au

	IY180	IY240	IY280
Control Option	Aries	Aries	Aries
Drum			
Capacity (kg)	18	24	28
Volume (L)	180	240	280
Door Opening	Ø 460 mm	Ø 460 mm	Ø 460 mm
Spin Type	High Speed	High Speed	High Speed
Install Requirements			
Electrical Requirements	32 Amp – 415 Volt – 3-phase Isolating Switch at 1.8m off floor	40 Amp – 415 Volt – 3-phase Isolating Switch at 1.8m off floor	50 Amp – 415 Volt – 3-phase Isolating Switch at 1.8m off floor
Water Recommendations (Hot)	1x Standard 19mm Washing Machine Tap	1x Standard 19mm Washing Machine Tap	1x Standard 19mm Washing Machine Tap
Water Recommendations (Cold)	2x Standard 19mm Washing Machine Tap	2x Standard 19mm Washing Machine Tap	2x Standard 19mm Washing Machine Tap
Water Pressure	Minimum = 44PSI (3 Bar) Maximum = 72PSI (5 Bar)	Minimum = 44PSI (3 Bar) Maximum = 72PSI (5 Bar)	Minimum = 44PSI (3 Bar) Maximum = 72PSI (5 Bar)
Drain	Ø 76mm through floor	Ø 76mm through floor	Ø 76mm through floor
Foundations	Minimum 100mm M20 Grade Concrete	Minimum 100mm M20 Grade Concrete	Minimum 100mm M20 Grade Concrete
Transport Data			
Gross Weight (KG)	395	450	515
Net Weight (KG)	380	430	495
Dimensions (mm)	1410 (h) x 970 (w) x 970 (d)	1410 (h) x 970 (w) x 1105 (d)	1410 (h) x 970 (w) x 1185 (d)
Packing Dimensions (mm)	1550 (h) x 1025 (w) x 1015 (d)	1550 (h) x 1025 (w) x 1150 (d)	1550 (h) x 1025 (w) x 1225 (d)
Optional Plinth	360 mm (height) 6 mm (thickness) Ø 16 mm (bolt hole)	360 mm (height) 6 mm (thickness) Ø 16 mm (bolt hole)	360 mm (height) 6 mm (thickness) Ø 16 mm (bolt hole)

(MM)	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
IY180	970	906	1410	970	477	270	108.5	1215	1297.5	102.5	208	293	610	1315	24
IY240	970	1041	1410	1105	477	270	108.5	1215	1297.5	102.5	208	293	610	1315	24
IY280	970	1116	1410	1185	477	270	108.5	1215	1305	102.5	208	293	610	1315	24

